

PDSI #12.3/N110-M



General Description

Power Rating	: 1.500 HP
Rated Hook Load	: Capacity 750.000 lbs
Drilling Depth	: 12.000 FT of 5" Drill Pipe
Servicing Depth	: 16.000 FT of 2 7/8" Tubing EU
Rig Flor Height	: 9.20 m
Mast Type	: National Oilwell USA Beam Leg Cantilever Mast M 142 25 – 1330, Pyramid
Substructure Type	: National 110 M Sling Shot 1000-25 set back, National

Drilling Equipment

Drawwork Type	: National OW 1500HP N=110-M, National
Rotary Table Type	: Rotary Table C-275,27 1/2", National
Mud Pump	: 2 Unit 10-P-130, National
Solid Control	
Shale Shaker	: 3 Unit Shaker Derrick FIC 513
Desander	: Cap, 800 gpm
Desilter	: Cap. 800 gpm

Storage Capacity

Mud Tank	: 3 Unit Mud Tank
Volume	: (Dimensi @ P9,18M X L.2,50 M X 250 M)

BOP Equipment

1 unit Annular BOP 13.5/8" x 10.000 PSI, HYDRIL, GX ABOP
1 unit Annular BOP 13 5/8" x 10000, GK, HYDRIL
1 unit Annular BOP 7 1/16' x 5000
1 unit BOP Single Ram Type "U" 21-1/4" x 2000 PSI
1 unit BOP Douzm Type "U" 13.5/8" x 5000, CAMERON
1 unit BOP Double Ram Type "U" 20" x 2000 PSI, SR

Power Equipment

Engine	2 unit Cat D-3516, for Mud Pump
	2 unit Cat D-3516, for Mud Pump
	1 unit Cat D-333
	1 unit Cat 3406

Cranes & Heavy Transport Equipment