

● PDSI #22.2/OW700-M



General Description

Power Rating	: 700 HP
Rate Hook Load	: 600.000 lbs
Drilling Depth	: 9.000 ft of 5" Drill Pipe
Servicing Depth	: 10.000 ft of 3 1/2" Drill Pipe
Rig Flor Height	: 7.65 m
Mast Type	: Heli Cantileve Mast 10 Segment Cap 600.000 lbs, pyramid
SubstructureType	: Elevated Floor / Sling Shot 700.000 lbs, Pyramid

Driling Equipment

Drawwork Type	: Double Drum Type M-700, National
Rotary Table Type	: Rotary Table C.275, 27 1/2" Full Open, National
Slush Pump	: 3 unit 10P-130, NOV
	: 1 unit 9-P 100, National
	: 1 unit 8 P 80, National
	: 1 unit PZ-9, Gardner Denver
Solid Control	
* Shale Shaker	: 3 unit King Cobra "S" (1.600 gpm), Brandt
* Desander	: 1 unit 10-DSV-2, Derrick
* Desilter	: 1 unit S-420-S Derrick
* Mud Claaner	: 1 unit SMC-10 (600 gpm), Brandt

Storage Capacity

Mud Tank Volume	: 6 unit Mud Tank (Total Cap . 724 bbls)
-----------------	---

BOP Equipment

1 unit Annular BOP 21 1/4 "x 2.000 psi, Hydrill
1 unit Annular BOP 13 5/8" x 5.000 psi, Hydrill
1 unit Annular BOP 7 1/16" - 5.000 psi Hydrill
1 unit BOP Double Ram 13 5/8"- 5.000 psi, WOM
1 unit BOP Double Ram 7 1/16"- 5.000 psi, Cameron

Power Eequipment

Engine	Generator
1 unit Cat D-3516 D-3512	2 unit GENSET, 600 KVA 480 KW 400 V 3 Phase 50 Hz 1500 RPM
4 unit Cat D- 3512	1 unit GENSET 500 F, 480 KW 400/230 V 3 Phase 50 Hz Sn.L4BZ02973
2 unit Cat D-3412	
1 unit Cat D- 3306	
2 unit Cat D- 379	
1 unit DEUTZ	

Cranes & Heavy Transport Equipment