



General Description

Power Rating	: 1.500 HP
Rated Hook Load	: 750.000 lbs (340Ton)
Drilling Depth	: 16.000ft of 5" Drill Pipe
Servicing Depth	: 20.000ft of 3.5" EUE Tubing
Ring Flor Height	: 30 ft (9.144 m)
Mast ype	: Mast Model 142' – 4 Section
Substructure Type	: Slingshot API 4F 3 RD Edition, DRECO

Drilling Equipment

Drawwork Type	: DSGD-375-2300-28-56-12L-6H, NOVI
Rotary Table Type	: Independent Rotary Table Drive Consisting of high
Slush Pump Type	: 3 unit 10P-130, NOV
Solid Control	
* Shale Shaker	: 3 unit Brandt King Cobra
* Desander	: 1 unit MN. SRS-3 / Hydrocyclone, NOV
* Desilter	: 1 unit Desilter, NOV
* Mud Cleaner	: 1 unit King Cobra 16 / Hydrocyclone, NOV

Storage Capacity

Mud Tank Volume	: 4 unit Mud Tank (Total cap. 1325 Bbls)
	: 1 unit Mud Tank (Shaker Tank)

BOP Equipment

1 unit Annular BOP 21 1/4 x 2.000 Psi
1 unit Annular BOP 13 5/8" x 10000 Psi
1 unit BOP Single Ram Type "U" 21-1/4" x 2000 Psi
1 unit BOP Single Ram Type "U" 13.5/8" x 10000 Psi
1 unit BOP Double Ram Type "U" 13.5/8" x 2000 Psi

Power Equeipment

Engine	Generator
4 Unit Engine, CAT 3512 DITA, 1476 HP, 1200 RPM	1 unit GENSET, 50 kVA, SN:OLYPLEZ02607, Olympian Engine Perkin1 unit Cat D-334
	4 Unit Generator SR4B, 1750 kVA, 1200 RPM, 60HZ

Cranes & Heavy Transport Equipment