



General Description

Power Rating	: 1.500 HP
Rated Hook Load	: 750.000 lbs (340Ton)
Drilling Depth	: 16.000ft of 5" Drill Pipe
Servicing Depth	: 20.000ft of 3.5" EUE Tubing
Ring Flor Height	: 30 ft (9.144 m)
Mast ype	: 14221 - 1000B GNC Cantilever Mast (Mast Height : 142 ft)
Substructure Type	: Slingshot Substructure 4F 3 RD Edition, DRECO

Drilling Equipment

Drawwork Type	: DSGD-375-2300-28-56-12L-6H-375, National Oilwell Varco
Rotary Table Type	: Rotary Table D-375, NOV : 7 Units 10P -130, National Oilwell Varco : 2 Units 10P -130, Hydrill
Slush Pump Type	: 2 Units 10P -130, Marathon Electric : 3 Units 10P -130 Siemens : 1 Units 10p -130, Hunt Engine
Solid Control	
* Shale Shaker	: 3 unit Brandt King Cobra
* Desander	: 1 unit NOV brandt MN, SRS-3, NOV
* Desilter	: 1 unit Desilter, NOV
* Mud Cleaner	: 1 unit King Cobra H/C Mud On 16SE, NOV

Storage Capacity

Mud Tank Volume	: 4 unit Mud Tank (Total cap. 1325 Bbls)
	: 1 unit Mud Tank (Shaker Tank)

BOP Equipment

- 1 unit Annular BOP 29 1/2 x 500 Psi
- 1 unit Annular BOP 21 1/4" x 2000 Psi
- 1 unit Annular BOP 13 5/8" x 10.000 Psi
- 1 unit BOP Single Ram Type "U" 13.5/8" x 10.000 Psi
- 1 unit BOP Double Ram Type "U" 7 1/16" x 10.000 Psi
- 1 unit BOP Double Ram Type "U" 13.5/8" x 10.000 Psi
- 1 unit BOP Double Ram Type "U" 7 1/16" x 10.000 Psi

Power Equeipment

Engine	Generator
4 Unit Engine, CAT 3512 DITA, 1476 HP, 1200 RPM	4 Unit Generator SR4B, 1750 kVA, 1200 RPM, 60HZ
4 Unit CAT D-3412	-

Cranes & Heavy Transport Equipment