



General Description

Power Rating	: 1000 HP
Rate Hook Load	: 500.000 lbs Capacity
Drilling Depth	: 6.000 - 8.000 ft of 5" Drill Pipe
Servicing Depth	: 8.400 - 11.200 ft of 3.5" Drill Pipe
Rig Flor Height	: 7.62 m
Mast Type	: Cantilever Mast , National Oilwell Varco
SubstructureType	: Slingshot Substructure , National Oilwell Varco

Drilling Equipment

Drawwork Type	: Model DSGD -250-2300-28-56-12L-6H, National Oilwell Varco
Rotary Table Type	: Rotary Table C-275, National Oilwell Varco
Slush Pump Type	: 3 Units Mud Pump AC 9P100 1000 HP National Oilwell Varco
Solid Control	
* Shale Shaker	: 3 Unit Model : King Cobra National Oilwell Varco Brandt System Include : 3 x King Cobra Linear Motion Shaker
* Desander	: Model : SRS-3 / Hydrocydone National Oilwell Varco
* Desilter	: Model : SE -20 / Hydrocydone National Oilwell Varco
* Mud Cleaner	: Model : King Cobra 16 / Hydrocydone National Oilwell Varco

Storage Capacity

Mud Tank Volume	: 4 Units (Total Cap. 1240 bbls)
	: 2 Units Mud Transfer pump 50 HP6 x 5 x 14 NOV

BOP Equipment

Annular BOP -21 1/4" - 2000 Psi Model	: Bolted Cover Spherical BOP
Annular BOP -13 5/8" - 5000 Psi Model	: Bolted Cover Spherical BOP
Annular BOP -7 1/16" - 5000 Psi Model	: Bolted Cover Spherical BOP
BOP Single Ram 13 5/8" x 5000Psi	
BOP Single Ram Type "U" 13 5/8" x 5000 Psi	
Single Ram BOP 20" -2000 Psi Model	: "WU" .BOP
Single Ram BOP 13 5/8" - 5000 Psi Model	: "WU" .BOP
Double Ram BOP 13 5/8" -5000 Psi Model	: "WU" .BOP
Double Ram BOP 7 1/16" - 5000 Psi Model	: "WU" .BOP

Power Equipment

Engine	Generator
3 Units CAT D-3512	2 Units GENSET 1 Olympian 50 KVA
	3 Units National Oilwell Varco Baylor. Model : S637UUT-20FH, 3PH, 60 HZ, 1200 RPM 600 Volt

Cranes & Heavy Transport Equipment