



General Specification



General Description		BOP Equipment	
Power Rating	: 700 HP	BOP Equipment	:
Rated Hook Load	: Capacity 265 ton	- 1 unit Annular BOP 20" x 2000 Psi, MSP	
Drilling Depth	: 9.000 ft of 5" Grade G 19.5 ppf	- 1 unit Annular BOP 20" x 2000 Psi, GK, Hydrill	
Servicing Depth	: 10.000 ft of 3 1/2" Tubing EUE	- 1 unit Annular BOP 13 5/8" x 5000 Psi, GK, Hydrill	
Rig Flor Height	: 7.60 m	- 1 unit Annular BOP 13 5/8" x 5000 Psi, S, Stewart	
Mast Type	: HeliRig Cantilver Mast, 10 Segmen, Cap. 600.000 lbs, Pyramid,	- 1 unit Annular BOP 7-1/16" x 3000 Psi, GK, Hydrill	
Substructure Type	: 25 feet Tip-Up, Cap. 480.000 lbs Pipe Set Back Cap. 600.000 lbs, Pyramid	- 3 unit BOP Double Ram Type "U" 13 5/8" x 5000 Psi	
Drilling Equipment		Power Equipment	
Drawwork Type	: Double Drum M-700, 700 HP	Engine	:
Rotary Table Type	: Rotary Table C-275, 27.1/2" Full Open, National	- 1 unit Cat D-3306, for Water Pump	
Slush Pump Type	: 3 Unit PZ-9, Gardner Denver	- 1 unit Cat D-3304, for Genset	
Solid Control	:	- 1 unit DETROIT 8V71	
- Shale Shaker	: 1 unit Cobra "King", Brandt	- 3 unit Cat D-379	
- Desander	: -	- 1 unit Cat D-399	
- Desilter	: -	- 2 unit Cat D-3412, for Genset	
- Mud Cleaner	: 1 unit Mud Cleaner, Derrick	- 1 unit Cat D-3406	
		- 2 unit Cat D-3512	
Storage Capacity		Generator	:
Mud Tank Volume	: 5 unit Mud Tank (Total Cap. 1375 Bbls)	- 2 unit GENSET SR4B, S/N : 8WW00931	
		- 1 unit GENSET S/N : 7ZS4415	
		Cranes & Heavy Transport Equipment	