



General Specification



General Description		BOP Equipment	
Power Rating	: 250 HP	BOP Equipment	:
Rated Hook Load	: Capacity 100.000 lbs	- 1 unit Annular BOP 7-1/16" x 3000 Psi, GK, Hydrill	
Drilling Depth	: 4.000 FT of 2 7/8" Drill Pipe	- 1 unit BOP Single Ram Type "U" 7 1/16" x 3.000 Psi, Koomey	
Servicing Depth	: 5.000 FT of 2 7/8" Tubing EU	Power Equipment	
Rig Flor Height	: 4 m	Engine	:
Mast Type	: Telescoping Cardwel CW-100-65, Cap 100.000 Lbs, Cardwel	- 1 unit SULLAIR, for Genset	
Substructure Type	: Ohara, H-2,6 M, W-4.50 M, L - 5.30 M	- 1 unit Cat D-3306, for Drawwork	
Drilling Equipment		- 2 unit Cat D-3408, for Mud Pump	
Drawwork Type	: Drawwork KM 200A - 57, 250 HP, Drum size 8.1/2" - 13"	- 1 unit PERKINS, for Welding Machine	
Rotary Table Type	: Rotary Table A-12 "KACKER" Chain RS-140-1 Rotary Drive Jack Shaft	- 2 unit DETROIT 6V71, for Genset	
Mud Pump	: 1 unit PZ 7, Gardner Denver	- 1 unit YANMAR, for Genset	
Solid Control	:	Generator	: -
- Shale Shaker	: -	Cranes & Heavy Transport Equipment	
- Desander	: -		
- Desilter	: -		
- Mud Cleaner	: -		
Storage Capacity			
Mud Tank Volume	: 2 unit Mud Tank (Total Cap. 70 m3)		