

General Specification



General Description		BOP Equipment	
Power Rating	: 400 HP	BOP Equipment	:
Rated Hook Load	: Capacity 250.000 lbs	- 1 unit Annular BOP 13 5/8" x 5000 Psi, Hydrill	
Drilling Depth	: 4.300 ft of 4 1/2" Drill Pipe	- 1 unit Annular BOP 11" x 3000 Psi, S, Stewart Stevenson	
Servicing Depth	: 8.500 ft of 2 7/8" Tubing	- 1 unit Annular BOP 7-1/16" x 5000 Psi, GK, Hydrill	
Rig Flor Height	: 4.40 m	- 1 unit BOP Single RAM Type "J" 7-1/16" x 5000 Psi, Line Koomey	
Mast Type	: Two section telescoping open face, 103 Ft height, Hook load cap. 230.000 lbs on 1" - 6 line	- 1 unit BOP Double Ram 13 5/8" x 5000 Psi	
Substructure Type	: Quick move skid mounted, Load capacity 200 T, Cardwell	- 1 unit BOP Double RAM Type "U" 11" x 3000 Psi, Cameron	
		- 1 unit Double Ram BOP Type "U" 7 1/16" - 3.000 Psi, Cameron	
Drilling Equipment		Power Equipment	
Drawwork Type	: Double Drum Cardwell T125 Trailler Carrier, 400 HP Cardwell	Engine	:
Rotary Table Type	: Rotary Table, 17 1/2" opening, Gardner Denver	- 2 unit Cat D-3406, for Genset	
Slush Pump Type	: 2 unit PZ 9, Gardner Denver	- 2 unit Cat D-3512, for Mud Pump	
Solid Control	:	Generator	:
- Shale Shaker	: 2 Unit FLC 513, 800 gpm, Derrick	- 2 unit GENSET 337 Kva, S/N CXE90201	
- Desander	: 1 unit Desander 4 Cone, Derrick	- 1 unit GENSET Silent GEP50-5, 50 KVA,SN: OLY00000CE3D00627, Olympian	
- Desilter	: 1 unit Desilter Mdl. 6T4, 900 GPM		
- Mud Cleaner	: 1 unit Model 2E48-120F-4T4, Floline, SWACO		
Storage Capacity		Cranes & Heavy Transport Equipment	
Mud Tank Volume	: 3 unit Mud Tank (Total Cap. 120 Ton)		