

● PDSI #20.2/EMSCOD2-M



General Description

Power Rating	: 750 HP
Rate Hook Load	: Capacity 725.000 lbs
Drilling Depth	: 8.000 FT of 5" Drill Pipe
Servicing Depth	: 12.000 FT of 3 1/2" Tubing EU
Rig Flor Height	: 6.50 m
Mast Type	: Cantilever CRL-142/136 ft
SubstructureType	: Birder 500.000 lbs

Drilling Equipment

Drawwork Type	: Drawwork Emsco-D2, 750 HP
Rotary Table Type	: Rotary Table C-275, 27 1/2", National Oilwell
Mud Pump	: 2 Unit 9P100,National : 1 Unit F-800, Emsco
Solid Control	
* Shale Shaker	: 3 Unit Brandt King Cobra, Total Cap 2400 gpm,Brandt
* Desander	: 1 Unit Desander Cap 800 gpm, Swaco
* Desilter	: 1 Unit Swaco 8 T 4, Cap 800 gpm, Swaco
* Mud Cleaner	: 1 Unit Mud Cleaner Brandt Cobra : 1 Unit Tri Flo International,300 gpm

Storage Capacity

Mud Tank Volume	: 4 Unit Mud Tank (Total Cap. 504 Bbls)
-----------------	---

BOP Equipment

1 Unit Annular BOP 20" x 2.000Psi, Hydrill
1 Unit Annular BOP 13 5/8" x 5.000Psi, GK, Hydrill
1 Unit Annular BOP 7 1/16" x 5.000Psi, GK, Hydrill
2 Unit BOP Single Ram Type "U" 13 5/8" x 5.000Psi, Cameron
1 Unit BOP Single Ram Type "U" 7 1/16" x 5.000Psi, Cameron

Power Equipment

Engine	Generator
2 Unit Cat D-3412 for GENSET	1 Unit GENSET SR-4 , Caterpillar
2 Unit Cat D-398	-
1 Unit Cat D-3512	-
4 Unit Cat D-379, For Mud Pump	-
1 Unit Cat D-3406, for Generator	-
2 Unit Cat D-334, for Mud Pump	-
3 Unit Cat D-3408, for Generator	-
1 Unit Cat D-3516, for Water Pump	-

Cranes & Heavy Transport Equipment

Crane	: One (1) Crane, Rated 50 tons
Hibed	: One (1) Hi Bed c/w Prime Mover
Tronton	: One (1) Tronton
Wheel Loader	: One (1) Wheel Loader, rated 8 tons