



General Description

Power Rating	: 1.500 HP
Rated Hook Load	: 750.000 lbs (340Ton)
Drilling Depth	: 16.000ft of 5" Drill Pipe
Servicing Depth	: 20.000ft of 3.5" EUE Tubing
Ring Flor Height	: 30 ft (9.144 m)
Mast ype	: Dreco 142 ft Mast (43.28) Accomodate 180 stand of
Substructure Type	: Dreco Slingshot Substructure, 26 ft (79.2 m) clear height under rotary table, length : 33 ft - 10 inch (10.05), width : 25ft - 7 inch (7.62 m)
Setback Capacity	: 500.000 lbs (227 T)
Rotary Capacity	: 70

Drilling Equipment

Drawwork Type	: NOV Baylor CM628TUT P/N : CM626TUT HN AL-2A1L1 (No.1) : NOV Baylor CM628TUT P/N : CM626TUT HN AL-2A1L1 (No.2)
Rotary Table Type	: NOV 37 1/2" Rotary Table with static load capacity 650 Ton
Slush Pump Type	: 3 unit of NOV 10-P-130 1300 HP AC motor driven, stroke length: 10" max press. 5000 Psi
Solid Control	
* Shale Shaker	: 3 unit Brandt King Cobra
* Desander	: 1 unit Brandt desander
* Desilter	: 1 unit Desilter, NOV
* Mud Cleaner	: 1 unit Brandt Mud Cleaner

Storage Capacity

Mud Tank Volume	: 1500 bbls total with 7 units tanks
-----------------	--------------------------------------

BOP Equipment

Diverter	29 1/2" Annular 500 Psi
Single Ram & Annular	21-1/4" x 2.000Psi
Double Ram & Annular	13-5/8" x 10.000Psi
Double Ram & Annular	7-1/15" x 10.000Psi

Power Equipment

Engine	Generator
4 Unit Engine, CAT 3512 DITA, 1476 HP, 1200 RPM	4 Unit Generator SR4B, 1750 kVA, 1200RPM, 60HZ

Cranes & Heavy Transport Equipment