



General Specification



General Description		BOP Equipment	
Power Rating	: 1.000 HP	BOP Equipment	:
Rated Hook Load	: 400.000 lbs	- 1 unit Annular BOP 20" x 2000 Psi, MSP, Hydrill	
Drilling Depth	: Up to 6000-10.000ft of 4 1/2" Drill Pipe	- 1 unit Annular BOP 13-5/8" x 5.000 Psi, GK, Hydrill	
Rig Flor Height	: 4.85 m	- 1 unit BOP Double Ram Type "U" 13-5/8" x 5.000 Psi, Stewarts	
Mast Type	: Full View FM 133-400/133 ft		
Substructure Type	: Substructure Type Set Back, Cap. 600 Lbs		
Drilling Equipment		Power Equipment	
Drawwork Type	: Double Drums E-900 (Electrical System), IDECO	Engine	:
Rotary Table Type	: Rotary Table C-275, 27 1/2", NOV	- 2 unit CAT-D3306	
Slush Pump Type	: 3 Unit 9 P 100, National	- 1 unit CAT-D3304	
Solid Control	:	- 6 unit CAT D-398	
- Shale Shaker	: 3 unit Shale Shaker FLC-513, Derrick	Generator	:
- Desander	: 1 unit model 2/48-120F-4TA, Derrick	- 3 unit GENSET, 500 Kva / 50 Hz / 1500 Rpm	
- Mud Cleaner	: 1 unit Flow line cleaner model 448-120, Derrick	- 2 unit GENSET, General Electric	
		- 1 unit GENSET Silent Heavy Duty Industrial, 160 KW 200KVA, SN.OLY000C MPN 02497, Caterpillar	
Storage Capacity		Cranes & Heavy Transport Equipment	
Mud Tank Volume	: 5 unit Mud Tank (Total Cap. 995 bbls)		