



General Specification



General Description		BOP Equipment	
Power Rating	: 1.000 HP	BOP Equipment	:
Rated Hook Load	: 280.000 lbs	- 1 unit Annular BOP 21 1/4" x 2000 Psi, Hydril	
Drilling Depth	: Up to 7.960 ft of 5" & 4 1/2" Drill Pipe	- 2 unit Annular 13 5/8" x 5000 Psi, GK, Hydril	
Servicing Depth	: Up to 9.000 ft of 2 7/8" Tubing EU		
Rig Flor Height	: 5.6 m		
Mast Type	: Lee C. Moore Cantilever 142 ft (550.000 lbs)	Power Equipment	
Substructure Type	: Double Box 8' H x 6' W x 28' L (350 Ton), National	Engine	:
Drilling Equipment		- 2 unit CAT D-3516, for Mud Pump	
Drawwork Type	: - National 80B1000 HP-7000 s/d 9500 ft, National - National 80 B 750 HP-6000 s/d 9000 ft, National	- 2 unit CAT D-3306, for Water Pump	
Rotary Table Type	: - Rotary Table C-275, 27. 1/2", National	- 3 unit CAT D-3412, for Mud Pump	
Slush Pump Type	: - 3 unit 9 P 100/1.000 HP, National - 1 unit 10 P 130, National	- 3 unit CAT D-3512, for Mud Pump	
Solid Control	:	- 3 unit CAT D-398	
- Shale Shaker	: - 3 unit FLC-513, Total Cap. 1650 Gpm, Derrick - 2 unit VSM-100, Total Cap. 1600 Gpm - 1 unit Triplex King Kobra, NOV	- 1 unit CAT D-343	
- Desander	: - 1 unit 10-DSV-2, Derrick - 1 unit Mission5 x 6R, Swaco	- 1 unit MITSUBISHI	
- Desilter	: - 1 unit T19, 800 GPM, Swaco	- 1 unit CAT D-3406	
- Mud Cleaner	: - 1 unit Flc 504, Derrick - 1 unit King Kobra Basket - 1 unit Tri Flo International		
Storage Capacity		Cranes & Heavy Transport Equipment	
Mud Tank Volume	: 4 unit Mud Tank (Total Cap. 160 m3)		